



Established in
1927

INSTITUTE OF PRECISION MECHANICS

Certification Department

01-796 Warszawa, ul. Duchnicka 3

phone (22) 663-43-24, (22) 663-43-14

fax (22) 560-29-22

e-mail: marek.zietala@imp.edu.pl

<http://www.imp.edu.pl/cert>



AC 041

CERTIFICATE OF CONFORMITY

No. P41/251/2015 (6347)

ENGLISH EDITION

Name and address of the certificate owner:	Inter - Sicherheits - Service Sp. z o. o. 66-400 GORZÓW WLKP., ul. Kobylogórska 2
Name and address of the manufacturer:	Inter - Sicherheits - Service Sp. z o. o. 66-400 GORZÓW WLKP., ul. Kobylogórska 2
Product name:	Deposit safe
Type (variants):	ELMSHORN Detailed information about dimensions and masses on the reverse
Main features:	Product class: - D-IV -
PKWiU symbol:	25.99.21.0
The product is in accordance with:	PN-EN 1143-2: 2014-06
According to the report issued by:	Search Laboratory for Mechanical Security Products of Institute of Precision Mechanics (Cert. of Accr. AB035)
Date of expiration:	June 28, 2018 The certificate is valid only with the identification label made specifically for this product
Rights for using this certificate from June 29, 2015 until June 28, 2018 refer only to products having identical parameters as sample(s) shown for inspection and meeting requirements stated in application No. 074/W/2015. This document is an equivalent of authentication of conformity with the standard acc. to the Regulation of Ministry of Internal Affairs dated September 7, 2010.	
Certification of conformity Type „3” acc. to PN-EN ISO/IEC 17067: 2014-01. Certificate of conformity issued acc. to the program PC-01 (IMP) – edition No. 8, May 15, 2015.	

MANAGER

Certification Department

Marek ZIĘTAŁA M.Sc. Eng.



DIRECTOR

Institute of Precision Mechanics

Tomasz BABUL Ph.D. D.Sc. Eng, prof. IMP

Certificate can be published only by Certificate Owner without comments, abbreviations and changes.

Warsaw, June 29, 2015.

No. P41/251/2015 (6347)

ELMSHORN safes (class D-IV acc. to PN-EN 1143-2: 2014-06) - basic parameters

Outer dimensions (mm)			Mass
height	width	depth	kg
800	650	550	494
1000	650	550	599
1200	650	550	704
1400	650	550	809

1000	650	550	599
1200	650	550	704
1400	650	550	809


Range of allowable dimensions:

Height: 550 ÷ 1800 mm;

Width: 496 ÷ 1000 mm;

Depth: 410 ÷ 950 mm

KIEROWNIK
Zakładu Certyfikacji


mgr inż. Marek Ziętała